

歐品電子(昆山)有限公司

OUPHIN ELECTRONIC(KUNSHAN) CO.,LTD.

PACKAGING SPECIFICATION (包 裝 作 業 規 范)

☒ CONFIDENTIAL ☐ TOP SECRET

SPEC.NO.(規範編號)	Q2386SPP-1091									PAGE	1/4	REV.	F
APPLICABLE CUSTOMER (適用客戶)	ALL	APPLICABLE PRODUCT (適用產品)	2386-12X60Cx DxMxT-x(-OP1)							PACKAGING CATEGORY (包裝方式)		TAPE REEL	

REVISE HISTORY (修 訂 履 歷)

REV. ECN NO.	頁 次 PAGE								
	1	2	3	4					
A	NEW 新版發行								
B	Modify the Code (修改编码)								
C	Add P/N (新增料號)								
D	Modify Placement Mode (修改包材放置方式)								
E	Modify the COVER (修改上帶)								
F	Modify Placement Mode (修改包材放置方式)								

DIVISION (事業單位)	Product Develop (產發部產品開發課)	APPROVED (核 准)		CHECKED (審 核)	PE: DE:	PREPARED (制 表)	WP 07/04'25
--------------------	-------------------------------	-------------------	--	------------------	------------	-------------------	-------------

歐品電子(昆山)有限公司

OUPIN ELECTRONIC(KUNSHAN) CO.,LTD.

PACKAGING SPECIFICATION (包裝作業規範)

CONFIDENTIAL TOP SECRET

PAGE 2/4 REV. F


SPEC.NO.(規範編號) Q2386SPP-1091

PACKING OPERATION DIAGRAM & INSTRUCTION (包裝作業圖示及說明)




REMARK (備注)

Heat plastic-band packing manner
封帶包裝方式

The road hole must be laid at the right of the drawing direction.
(導向圓孔必須設在拉延方向的右側)



The begining of the band , the detailed chart of the end.
(封帶開始部分，結束部分的詳細圖)



一.Packing of interior box:
(內盒包裝方式)

- (1)Packaging way of each reel is shown in drawingone.
(每個REEL包裝方式,如圖(一)所示)
- (2) At the beginning of winding belt,take one part of sticky belt with 60 mm length,15mm width. stick 20 mm on the material belt,stick 40 mm on the gap of the REEL mandrel , as shown in drawing two.
(在開始纏繞料帶時,取長60mm寬15mm之膠帶一段, 20mm 黏于料帶上, 40mm 黏于REEL心軸之缺口上,如圖(二)所示)
- (3) Use one REEL can package 300 PCS products .
(每卷REEL可包裝300PCS產品)
- (4)After winding the material belt, stick the COVER TAPE with 60 mmlength, 15 mm width stick belt, and fix it on the circumference of the REEL,as shown in drawing three.
(料帶卷繞完成時取長60mm寬15mm之3M膠帶黏住COVER TAPE并將其固定在REEL之圓周上,如圖(三)所示)
- *. Stick sticky belt(18mm width,40 length) on the two sides when COVER TAPE is interrupted, stick each end with20 mm belt to get them together.and the two COVER TAPE connected must be at the same line.
(COVER TAPE 有中斷時可用寬18mm,長40mm之膠帶將中斷之兩端各貼20mm,使其連接為一體. 但連接后的兩段COVER TAPE應在同一直線上.)

歐品電子(昆山)有限公司

OUPIIN ELECTRONIC(KUNSHAN) CO.,LTD.

PACKAGING SPECIFICATION (包裝作業規範)


CONFIDENTIAL TOP SECRET

PAGE 3/4 REV. F

SPEC.NO.(規範編號) Q2386SPP-1091

PACKING OPERATION DIAGRAM & INSTRUCTION (包裝作業圖示及說明)

REMARK (備注)



2.Outer box packing mode:

(二.外箱包裝方式)

- (1)Paper box(CT-1.5)1PCS(Drawing Six).
(紙箱CT-1.5 1PCS(圖六))
- (2).Put 1pcs allocating paper board at the bottom of the box ,
then put 1 PCS waterproof bag on the board(Drawing Six).
(底層放入紙箱配套紙板1PCS.上面放入防水袋1PCS(圖六))
- (3).Each the reel paste three the scotch tape ,After folding XXpieces of reel disk.
seal the waterproof bag(Drawing Five).
(將每個Reel盤封上三道透明膠帶，疊好XX個Reel盤後封上防水袋(圖五))
- (4).Put 1PCS double decked paper board on the top of box(Drawing Four).
(最上層放入雙層紙板1PCS(圖四))
- (5)*The box must be filled up completely without any gaps, fill the gaps with
Air column bags.
(*箱內必須要填滿不能有空隙，空隙用氣柱袋填滿。)
- (6)Seal the surface of the outer box (Drawing Seven).
(將外箱上層封口(圖七))

*The form on the right and flank side of the box must be filled correctly
and clearly,take actual testing weight as the standard of every box gross
weight.

(*外箱之正面和側面所要填寫之項目要填寫正確，
清晰,每箱之毛重應以實測重量為準。)

歐品電子(昆山)有限公司
OUPHIN ELECTRONIC(KUNSHAN) CO.,LTD.
PACKAGING SPECIFICATION (包裝作業規範)

☒CONFIDENTIAL ☐TOP SECRET

PAGE: 4/4 REV. F

SPEC.NO.(規範編號) Q2386SPP-1091

C	PACKING MATERIAL (包 裝 材 料)			PRODUCT P/N	TAPE REEL STANDARD	PACKING P/N	PACKING N.W.	PACKING QUANTITY (包裝數量)			WEIGHT (重 量) kg			C
	MATERIAL NAME (材料名稱)	PART NO. (料 號)	Q'TY	(產品料號)	(包材規格mm)	(包材料號)	(包材重量)	PCS/REEL	REEL/BOX	PCS/BOX	N.W./PCS	N.W./BOX	G.W./BOX	
	PAPER BOXES (紙箱)	CT-1.5	1	2386-12X60CxDxxMxT-x(-OP1)	88	2386-K12088-001	3.16	300	3	900	0.00455	4.10	7.26	
D	WATERPROOF BAG (防水袋)	100*70	1			COVER-K0088-002								
						REEL-K0088-001								
D	DOUBLE DECKED PAPER BOARD (雙層紙板)	340*340*5	2										D	
E	3M FIBER BELT (3M纖維膠帶)	-----	-----										E	
F	DRYING AGENT (干燥劑)	-----	3										F	
G	Air column bags 氣柱袋	-----	-----										G	
G														

1.NOTE:
(注意)
When the finished products have been made,take the actual weight as the standard of gross weight in each box.
(成品出貨時,每箱之毛重應以實測重量為準)
When the finished products have been made,stick the proper designation list on the box according to product demand.
(成品出貨時,依據出貨要求貼上相對應的標籤單)

2.NOTE:
(注意)
*Pay attention to each big reel of material ,can be divided into 3 small reels,consumption of each big reel can't exceed 1meter, or the third reel can't be packed
(來料每大卷reel (carrier tape) 平均可分3小卷reel , 每大卷reel 消耗量不可超過1米, 否則第三小卷不可包裝)