

REV.	SPECIFICATION	ECN NO.	APPD.
R4		ECN251215	

Material and Plating:

Housing: LCP, UL94V-0 , BLACK.

Power Contacts: High Conductivity Copper, Gold Plated or Au+Pd/Ni on Contact Area and 80u" Min Tin Plated on Press Fit over Nickel 50u" Min .

Electrical Characteristics:

Current Rating: Power Pin:100 A(2 Adjacent Contacts).

Dielectric Withstanding Voltage:



Power Pin DC 2500V For 1 minute.

Insulator Resistance: Power Pin 1000MΩ min.

Contact Resistance: Power Pin 0.3mΩ max.

Operating Temperature: -55°C ~+125°C .

***RoHS & HF Compliant**



P.C.Board Layout
(Tolerance:±0.05)

Tolerances	Dwg. No.	9311-0P02-002	Title:			
x = ±1	Projection		9311 Series PwrFULL [®] Female Straight Press Fit Type			
.x = ±0.5	Unit	mm				
.xx = ±0.25	Scale	1:1				
.xxx = ±0.10	Drawn By	XS 12/10'25				
			OUPIN ELECTRONIC(KUNSHAN) CO., LTD.			
			P/N: 9311-2P02B7PAA01			
			SHEET	1/1	Ver. No.	R4