



9391-A 2 P01 S24 P01 CB 30 D L A
 Series
 2: Female Straight
 Blank: Without Contact
 Power Contact: Hxx, Pxx, Axx
 No. of position
 Blank: Without Contact
 Signal Contact: S xx
 No. of position
 A: Tray Package
 L: With Lock
 Blank: Without Lock
 D: Dip Type
 30: 30u"
 CB: Dip Tin Plated
 Contact Au+Pd/Ni Plated
 Blank: Without Contact
 Power Contact: Hxx, Pxx, Axx
 No. of position

REV.	SPECIFICATION	ECN NO.	APPD.
R2		ECN260150	

Material and Plating:

Housing: LCP, UL94V-0, BLACK.
 Power Contacts: High Conductivity Copper.
 30u"Au+Pd/Ni on Contact Area and 80u" Min Tin Plated on Solder Tail over Nickel 50u" Min .
 Signal Contact: Phosphor Bronze.
 30u"Au+Pd/Ni on Contact Area and 80u" Min Tin Plated on Solder Tail over Nickel 50u" Min .

Electrical Characteristics:

Current Rating: Signal Pin 2.5 AMP.
 Power Pin 30 AMP.
 Dielectric Withstanding Voltage:
 Signal Pin DC 1000V For 1 minute.
 Power Pin DC 2500V For 1 minute.
 Insulator Resistance: Signal Pin 5000MΩ min. at DC 500V.
 Power Pin 20000MΩ min. at DC 500V.
 Contact Resistance: Signal Pin 15mΩ max. at DC 20mA.
 Power Pin 0.7mΩ max. at DC 20mA.
 Operating Temperature: -40°C ~+105°C .

***RoHS&HF Compliant**

Notes 1:

H: High density Power---PCB Mount 5.08mm Pitch
 P: DC Power---PCB Mount 6.35mm Pitch
 A: AC Power---PCB Mount 7.62mm Pitch
 S: Signal---PCB Mount 2.54mm Pitch

ROWS		POWER		SIGNAL				POWER		
		P2	6	5	4	3	2	1	P1	
D		FS	L	L	L	L	L	L	FS	
C			L	L	L	L	L	L		
B			L	L	L	L	L	L		
A			L	L	L	L	L	L		

POWER CONTACT TO THE TOP DISTANCE 2.34mm,	FM
POWER CONTACT TO THE TOP DISTANCE 1.07mm,	FS
SIGNAL CONTACT 3.43 SOLDER TAIL, PD/Ni	L

Tolerances	Dwg. No.	9391-D0000-102		Title:	
x = ±0.5	Projection			9391 Series Female Straight Dip Type	
.x = ±0.25	Unit	mm	Scale		1:1
.xx = ±0.15	Drawn By	XM 01/23'26			

OUPIN ELECTRONIC(KUNSHAN) CO., LTD.			
P/N: 9391-A2P01S24P01CB30DLA			
SHEET	1/1	Ver. No.	R2